

## UK Declaration of Performance

### Inno-Fix

1000.UKDoP.IF.002 1001.UKDoP.IF.002

Unique identification code of the product-type:

**Inno-Fix**

Intended use/es:

**Thermal insulation for buildings**

Manufacturer:

**EcoTherm Insulation (UK) Ltd, Harvey Road, Basildon, SS13 1QJ**

System/s of AVCP:

**System 4 (Reaction to fire), System 3 (Other Properties)**

Designated technical specification:

**BS-EN 13165:2012+A2:2016**

UK Assessment body/ies:

**University of Salford: 1145, BBA : 0836, BITS: 1334**

Essential characteristics		Performance	
Thermal resistance	Thermal resistance $R_D$ ((m <sup>2</sup> .K)/W)	$d_N$ 30mm	1.35
		$d_N$ 40mm	1.80
		$d_N$ 50mm	2.25
$d_N$ 60mm		2.70	
$d_N$ 70mm		3.15	
$d_N$ 80mm		3.60	
$d_N$ 90mm		4.05	
$d_N$ 100mm		4.50	
$d_N$ 120mm		5.45	
$d_N$ 130mm		5.90	
$d_N$ 140mm		6.35	
$d_N$ 150mm		6.80	
$d_N$ 160mm		7.25	
	Thermal conductivity $\lambda_D$ (W/(m.K))	$d_N$ 25-160mm	0.022
	Thickness tolerance		T2
Reaction to fire	Reaction to fire		F
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability of the reaction to fire of the product as placed on the market		NPD
	Durability of thermal resistance and thermal conductivity against ageing/ degradation		NPD
Durability of Thermal Resistance against heat, weathering, ageing / degradation	Thermal resistance $R_D$ ((m <sup>2</sup> .K)/W)	Thermal resistance as table above	
	Thermal conductivity $\lambda_D$ (W/(m.K))	0.022	
	Durability characteristics	NPD	
	Dimensional stability under specified temperature and humidity condition	DS(70,90)3 DS(-20,-)1	
	Deformation under specified compressive load and temperature conditions	NPD	

## UK Declaration of Performance

### Inno-Fix

	Determination of the aged values of thermal resistance and thermal conductivity	$\lambda_D$ 0,022 W/m·K
Compressive strength	Compressive stress or compressive strength	CS(10\Y)150
Tensile / Flexural strength	Tensile strength perpendicular to faces	TR40
Durability of compressive strength against ageing / degradation	Compressive creep	NPD
Water permeability	Short term water absorption	NPD
	Long term water absorption	NPD
	Flatness after one sided wetting	NPD
Water vapour permeability	Water vapour transmission	NPD
Acoustic absorption index	Sound absorption	NPD
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD
NPD: No Performance Determined		

Signed for and on behalf of the manufacturer by:



.....  
**Ralph Mannion**  
**Managing Director**  
**Pembridge, Selby England, UK**  
**Date signed: 18 / 01 / 2022**  
**Issue Number: 002**

B:\GB\UKDoP\Inno-Fix\002\Jan22a