




Insulation



Product Safety Information

Therma™



Fibre-free
Core


Kingspan®

Product Safety Information

Therma™

Although the REACH Regulation does not require a Safety Data Sheet to be provided for Therma™ iSoEasy®, W'all-in-One®, SaunaSatu® & Selthaan® products, as they are considered articles under the Regulation, this Product Safety Information Sheet has been prepared to reflect the primary SDS requirements as set out in Annex II to Regulation (EC) No 1907/2006 (REACH), and amended by Commission Regulation (EU) No 2015/830 as they might reasonably apply to articles. The sole purpose of this information sheet is to provide additional information.

Section 1: Identification of the products and company

Product identifier

- | | |
|---|--|
| ■ Kingspan Therma™ TF70 Floorboard | ■ Kingspan Therma™ TW53 External Wall Board |
| ■ Kingspan Therma™ TP10 Pitched Roof Board | ■ Kingspan Therma™ TW55 Framing Board |
| ■ Kingspan Therma™ TP10 Renova Pitched Roof Board | ■ Kingspan Therma™ TW55 R Framing Board |
| ■ Kingspan Therma™ TP11 Pitched Roof Board | ■ Kingspan Therma™ TW56 Insulated Plasterboard |
| ■ Kingspan Therma™ TP12 Pitched Roof Board | ■ Kingspan Therma™ TW57 Rainscreen Board |
| ■ Kingspan Therma™ TR20 Flat Roof Board | ■ Kingspan Therma™ TW58 Concrete Element Board |
| ■ Kingspan Therma™ TR24 Flat Roof Board | ■ Kingspan iSoEasy® |
| ■ Kingspan Therma™ TR26 Flat Roof Board | ■ Kingspan W'all-in-One® |
| ■ Kingspan Therma™ TR27 Flat Roof Board | ■ Kingspan Sauna-Satu® |
| ■ Kingspan Therma™ TR28 Flat Roof Board | ■ Kingspan Selthaan® AirTec |
| ■ Kingspan Therma™ TT40 Tapered Roof Board | ■ Kingspan Selthaan® Alu |
| ■ Kingspan Therma™ TT46 Tapered Roof Board | ■ Kingspan Selthaan® Megaplug HD |
| ■ Kingspan Therma™ TT47 Tapered Roof Board | ■ Kingspan Selthaan® Megaplug SE |
| ■ Kingspan Therma™ TW50 Cavity Wall Board | ■ Kingspan Selthaan® Mehrlagen |

Relevant identified uses

Thermal insulation products for buildings.

Details of the Supplier of the Product Safety Information Sheet

Kingspan Insulation B.V.
Lorentzstraat 1
7102 JH Winterswijk, The Netherlands

T: +31 (0)543 543 210
F: +31 (0)543 530 844
E: techline@kingspaninsulation.eu
www.kingspaninsulation.eu

Product Safety Information

Therma™

Section 2: Hazards identification

- When used as intended, this product is classified as non-hazardous and there are no known toxic influences.
- When the material is cut, long-term exposure to the dust may lead to irritation of the skin, eyes and lungs. Eye and respiratory protection is always recommended. During large/industrial scale cutting and/or transformation of the material, local regulations regarding occupational exposure limits (OEL) of volatile substances and (fine) dust must be monitored. Mechanical ventilation and dust extraction may be necessary.
- The product is not classified as ecotoxic.

Section 3: Composition

Core

- Rigid thermoset polyurethane insulation (PUR or PIR as defined in EN 13165).

Alternative Facings

- Composite foil (TF70 – TP10 – TP10 Renova – TP11 – TR26 – TR28 – TT46 – TW50 – TW55 – TW56 – TW58 – iSoEasy® – W'all-in-One® – Sauna-Satu® – Selthaan® Alu – Briteboard – Mehrlagen)
- Alu stucco foil (Selthaan® Megaplust HD, Megaplust SE)
- Bitumen coated glass tissue (TR20 – TR24 – TT40)
- Glass tissue (TP12 – TW53)
- Coated glass tissue (TR24 – TR27 – TT47 – TW55 R – TW57 – Selthaan® AirTec)
- Fleece membrane (TP11 – TP12)
- Expandable (TW57)
- Plasterboard (TW56 – W'all-in-One®)
- Chipboard (iSoEasy®)

Section 4: First aid measures

- Inhalation: Dust is non-hazardous. Take the person to fresh air.
- Skin contact: Non-sensitising. When glass facing is handled, skin irritation may occur. In the event that irritation occurs wash carefully using soap and water or a proprietary cleanser to remove.
- Eye contact: Dust particles should be removed by flushing with clean water.
- Ingestion: Drink plenty of water and rinse.
- Other: Seek medical attention if discomfort persists.

Section 5: Firefighting measures

It is prudent to take precautions against ignition, fire spread and smoke hazard.

Extinguishing media

- Suitable extinguishing media: Water-based fire extinguishers (fog), foam, CO₂ or dry chemical.
- Unsuitable extinguishing media: Not applicable.

Advice for firefighters

Firefighters should use self-contained breathing apparatus and saturate burning foam with water from a spray nozzle. Sawdust is classified as weakly explosive (St. Class 1).

Section 6: Accidental release measures

Not applicable.

Product Safety Information

Therma™

Section 7: Handling and storage

- Keep contamination of workplaces as low as possible (e.g. to careful handling of products and waste). Store in original packing in a location free from any ignition hazard such as open flames, cutting and welding torches, high surface temperature electric heaters and other forms of direct radiant heat.
- Keep product protected from the elements. Ensure stability of stack and provide adequate aisle space for access between stacks.
- Keep in original packaging until ready for installation. All products should be stored inside a building or protected against weather influences and raised off the floor. Ensure stability of stacks and follow guidance instructions on packaging.

Section 8: Exposure controls/personal protection

- Inhalation: Dust is non-hazardous. As with all cutting procedures it is recommended that a disposable dust mask be worn. Masks of class FFP2 or better are recommended. Where dust is generated through mechanical cutting in confined spaces, it is recommended that extraction be used. It is recommended when non-mechanical cutting is carried out that the product is cut with a trimming knife to minimise the generation of dust.
- Hands: It is recommended that gloves be worn when handling the product. Materials combined with an aluminium sheet vapour barrier must be handled with gloves capable of protecting against cuts.
- Eyes: As with all cutting procedures it is recommended that eye protection be worn. When installing a product with reflective foil facings in very bright or sunny weather it is advisable to wear UV protective sunglasses or goggles.
- Skin: Non-sensitising. It is recommended to wear gloves when handling the product. When installing a product with reflective foil facings in very bright or sunny weather it is advisable to consider skin protection from UV.
- Other: The products are non-load bearing. Access and work should not be carried out on un-supported boards (TP10 TP11 TP12 can be carried out as un-supported boards when approved and fixed with manufacturers guidelines). The smooth facing used on some products can be slippery underfoot when wet. Be extremely careful and follow all safety precautions when you saw insulation boards by hand or with a machine.

Section 9: Physical and chemical properties

- Appearance: Yellow foam with composite foil, alu stucco foil, bitumen coated glass tissue, glass tissue, coated glass tissue, fleece membrane, plasterboard or chipboard.
- Physical state: Solid.
- Odour: Negligible.
- Melting point: Not applicable.
- Flash point: Not applicable.
- pH: Neutral under normal conditions.
- Insulation density: Typically 30 – 60 kg/m³.
- Solubility in water: Insoluble.
- Solubility in organics: Some liquids might cause swelling to the product.
- Other data: None.

Section 10: Stability and reactivity

Stable and inert during normal use (see section 7).

Section 11: Toxicological information

No known toxic effects when used normally and as intended. During large/industrial scale cutting and/or transformation of the material, local regulations regarding occupational exposure limits of volatile organic substances must be monitored. Mechanical ventilation and dust extraction may be necessary.

Section 12: Ecological information

The product is inert and stable in water and soil.

Product Safety Information

Therma™

Section 13: Disposal considerations

Waste insulation is non-hazardous and should be disposed of regularly in a designated location without grinding or powdering in accordance with local requirements and laws. Any product dust created in the installation process is regarded as nuisance dust only, because of its inert nature. It is important that the accumulation of waste insulation is avoided to prevent wind dispersal. Observe usual safety precautions with polythene bags, wrapping and packaging. Clean, undamaged product may be re-used. Insulation core waste is fully recyclable.

Section 14: Transport information

Read this section in conjunction with section 7. Ensure security of load and where necessary sheeting/roping should be used. It is recommended that mechanical lifting equipment is used when moving bulk quantities of product in order to avoid serious physical injury.

Section 15: Regulatory information

Properties according to EC directives

Not applicable.

Section 16: Other information

- The information contained here is offered in good faith and is based on our current knowledge. We thereby withhold the right to update and amend this document as necessary.
- The information should not be taken as guarantee of specific performance and users should make their own assessment and make all applicable personnel aware accordingly.
- All chemical products can affect persons with a sensitive or allergic disposition, persons with such sensitivity should seek medical advice before handling the product.
- The wearing of appropriate safety equipment is strongly recommended as a precaution and the product should only be used in its design application strictly in accordance with the directions given.
- Users should visit our website www.kingspaninsulation.eu or contact the Kingspan Insulation Technical Service Department to ensure information is current.

Contact Details

Head Quarters Continental Europe

Kingspan Insulation B.V.

Lorentzstraat 1
7102 JH Winterswijk
The Netherlands

T: +31 (0) 543 543 210

E: info@kingspaninsulation.eu

www.kingspaninsulation.eu

Services



Techline

(technical & calculation enquiries)

T: +31 800 25 25 252

E: techline@kingspaninsulation.eu



Tapered

(design related enquiries)

T: + 31 800 25 25 252

E: tapered@kingspaninsulation.eu

The physical and chemical properties of the products of Kingspan Insulation represent average values obtained by testing in accordance with generally accepted standards and are subject to standard tolerances. Kingspan Insulation reserves the right to amend product specifications and thicknesses without prior notice.
The information, calculations, technical details and fixing instructions included in any documentation or advice are given in good faith and apply only to uses described in this context. They are based on the information provided to us. Kingspan Insulation is not liable for damages in case of wrong and/or incomplete information provided. Furthermore, Kingspan Insulation does not guarantee a certain result.

The images in any document or advice are only meant to give a general impression of the appearance of the products and show one of the various possible applications. Kingspan Insulation does not guarantee that the shown applications are in accordance with valid (local) regulations in the country of use, are fit for your purpose or your intended use. Recommendations for use should always be verified for suitability and compliance with actual requirements, specifications and any applicable laws and regulations. For other applications or conditions of use, Kingspan Insulation offers a Technical Advisory Service, the advice of which should be sought for uses of Kingspan Insulation products that are not specifically described herein.

No claims, representations or warranties, whether express or implied, are made by Kingspan Insulation as to the use, safety, reliability, durability and performance of any of our products, unless explicitly stated. Furthermore, Kingspan Insulation accepts no liability whatsoever for the use, safety, reliability, durability and performance of any of our products, unless explicitly agreed in writing.

Please check that your copy of our literature is current by contacting the Kingspan Insulation Marketing Department.

© Kingspan, iSoEasy, SaunaSatu, Selthaan and the Lion Device are Registered Trademarks of the Kingspan Group plc in the EU and other countries. All rights reserved.

TM Therma is a Trademark of the Kingspan Group plc.

